



1040C

User Manual



INDEX

Preface	3
This product	3
Before use	5
Intended use	5
General safety instructions	5
Symbols on the wheelchair/commode chair	6
Storage	6
Using your wheelchair/commode chair	6
Armrest	7
Brakes	7
Comfort adjustments	8
Moving to/from the chair	9
Riding	9
Assembly and adjustments	10
Tools of delivery	10
Assembly	11
Adjustments	11
Maintenance	12
Points of maintenance	12
Instructions for maintenance	12
Troubleshooting	13
End of use	13
Technical specifications	13
Warranty & service	15



Preface

Congratulations! You are now owner of a Midmark wheelchair/commode chair!

This chair is made by qualified and committed personnel. It is designed and produced according to high quality standards, guarded by Midmark.

Please read this manual carefully; it will help you to get familiar with the operation, capabilities and limitations of your chair. If you still have questions after reading this manual, do not hesitate to contact your specialist dealer. He/she will be glad to help you.

Important note

To ensure your safety, and to prolong the lifetime of your product, please take good care of it and have it checked and serviced on a regular basis.

This manual reflects the latest product developments. Midmark has the right to implement changes to this type of product without any obligation to adapt or replace similar products previously delivered.

Pictures are used to clarify the instructions in this manual. Details of the depicted product may deviate from your product.

Information available

On our website <u>www.midmark.in</u> you will always find the <u>most recent version</u> of the information in this manual. Please consult this website regularly for possible updates.

Visually impaired people can download the electronic version of this manual and have it read out by means of a text-to-speech software application.

	Instruction manual	For user and specialist dealer
Ti.	Service manual for wheelchairs	For specialist dealer
	EC declaration of conformity	



This product

The wheelchair/commode chair of the 1040C is easy to operate. Their use depends



on the model. Table 1 of chapter 7 summarises the technical specifications of these models.

General characteristics:

- Metal alloy frame.
- Upholstery in washable and fireproof material.
- Reclining anatomic backrest with push bar; adjustable and removable.
- Padded and removable armrests.
- Footrests with operating lever.
- PVC bowl under seat (optional)
- Closing seal for seat with handle for

removal.

• The pictures on this page show all parts that are relevant for the user.



Before use

Intended use

In this paragraph a brief description of the intended use of your wheelchair/commode chair is given. Additionally, relevant warnings are added to the instructions in the other paragraphs. In this way we would like to make you aware of the possible misuse that may appear.

- Depending on the model, the wheelchair/commode chair is suitable for indoor and outdoor use or only for indoor use, see chapter 7.
- This wheelchair/commode chair is designed and produced solely as resting place and to transport/transfer one (1) person with a maximum weight of 100 kg.
- The chair is equipped with a seat with a removable part and two guiding strips for a PVC bowl, to be used as toilet. Without bowl, it can be used as toilet seat, but only if the toilet fits under the seat, see chapter 7 for dimensions.
- The chair is not designed to transport goods or objects, nor for any other use as previously described.
- The 1040C commode chairs should be operated by an attendant.
- You should NOT use this wheelchair/commode chair without attendant if you suffer from physical or mental impairments that may put you, or other people, in danger. For this reason, consult your doctor first and make sure that your specialist dealer is informed about his/her advice. This also counts for the attendant operating the chair.
- If applicable, only use accessories and spare parts approved by Midmark.
- The warranty of this product is based on normal use and maintenance as described in this manual. Damage to your product caused by improper use or lack of maintenance will cause the warranty to lapse.

Please read all technical details and limits of your wheelchair/commode chair in §7.

General safety instructions

CAUTION Risk of injuries and/or damage Please read and follow the instructions in this manual.

Keep the following general warnings in mind during use:

- Be aware that some parts of your wheelchair/commode chair may get very hot or cold due to ambient temperature, solar radiation or heating devices. Be careful when touching. Wear protective clothing if the weather is cold.
- Do not modify your wheelchair/commode chair in any way.
- Take note of the instructions for care and service. The manufacturer is not liable for damage caused by improper servicing / care.



Symbols on the wheelchair/commode chair

The symbols in following list are applicable for your wheelchair/commode chair/commode chair. Symbols can be found in the relevant ISO standard (ISO 7000, ISO 7001 and IEC 417)

Maximum weight of user in kg

Indoor/outdoor use

Maximum safe slope in ° (degrees).

Not intended to be used as seat in a motor vehicle

TYPE Type designation

Risk of entrapment

Storage

Make sure that your wheelchair/commode chair is stored clean and dry to prevent mould from growing or the upholstery from being damaged, see also chapter 7.

Using your wheelchair/commode chair

A CAUTION Risk of injuries and/or damage

- Make sure that your hands, clothes, belts, buckles or jewellery won't get caught by wheels or other moving parts, during use or adjustment.
- Always keep the swing range of the footplate in mind to prevent bystanders or objects from being damaged. from being injured



Armrest

To open:

• Pull lever (20) and swing the armrest (2) to the back.

To remove:

 Pull lever (20) and pull the armrest (2) upwards until it comes out of both tube hoods.

To install:

- 1. Mount the rear tube of the armrest in the tube hood (21).
- 2. Fold the armrest forward.
- 3. Pull the lever (20) while inserting the front tube in tube hood (22).
- 4. Check that the armrest is well tightened.



Brakes

 ⚠ CAUTION

Risk of injuries

- Depending on the location of the brakes, the brakes are operated by an attendant or by the user sitting in the chair. Never lean too far to the left or right trying to operate the brakes.
- Never release both brakes simultaneously.
- Do not use the parking brakes to slow the wheelchair/commode chair down during movements.
- Brakes may only be adjusted by your specialist dealer.


Your chair is equipped with two manually operated parking brakes. These brakes are intended to prevent movement of the chair when parked. Depending on the location of the brakes, they are operated by pushing or pulling the brake lever.

Parking brakes for 24" and 5"model Releasing brakes:

- Hold one hand rim tight with one hand (or your attendant holds the push bar with one hand).
- 2. Operate brake lever (8) of the OTHER wheel to release the wheel.
- 3. Repeat this for the second wheel and parking brake.

Applying brakes:

- 1. Hold one hand rim tight with one hand (or your attendant holds the push bar with one hand).
- 2. Operate brake lever (8) of the OTHER wheel until you feel a distinctive lock.






3. Repeat this for the second wheel and parking brake.

Parking brakes for swivelling wheels Releasing brakes [C]:

Use your foot to press the top of the brake lever backwards. Applying brakes [D]:

Use your foot to press the brake lever down towards the castor wheel.



Comfort adjustments

Risk of injuries and damage

- Always keep the swing range of footrest in mind to prevent bystanders from getting injured or objects from being damaged.
- Make sure that your fingers, clothes, buckles won't get entrapped during adjustment.

Adjust backrest inclination

- 1. Loosen both locking knobs (17) of the adjustment system, at left and right side. The backrest will move to the front.
- 2. Push the backrest in position and lock the position by tightening both locking knobs (17) firmly.
- 3. Check by moving the backrest.



Leg rest inclination

- To raise: Pull the leg rest (12) up to the desired height.
- To lower: hold the footrest with one hand and push the operating lever (26) to release the leg rest. Lower the leg rest up to the desired height and release the operating lever (26).





Moving to/ from the chair



Risk of injuries and damage

In case you cannot perform the transfer in a safe manner, ask someone to assist you.

Do not stand on the footplates during transfer into or out of the wheelchair/commode chair.

Transfer

- 1. Position the wheelchair/commode chair as close as possible to you when sitting in your chair, couch, seat or bed.
- 1. Apply both parking brakes to block the movement, see §4.2.
- 2. Fold the footplates upwards to prevent standing on them.
- 3. If the transfer is on the side of the wheelchair, turn the arm rest on that side upwards.
- 4. Transfer to/from the wheelchair/commode chair using the strength of your arms or with the help of attendant(s) or lifting equipment.

 Sitting in the wheelchair/commode chair
- 1. Sit down on the seat with your lower back against the backrest.
- 2. Turn the footplate down and put your feet on the footplate.

Riding



Risk of injuries and damage

- Before every usage, make sure that:
 - footplate adjustment is firmly secured, see §5.4.2.
 o parking brakes are working properly.
 - o tires are in good condition, see §7.
- Prevent your fingers from being caught by the wheel spokes.
- Do not operate the hand rims with wet hands.
- Prevent entrapment of your hands on the hand rims when you pass small passages.
- Do NOT drive on slopes, obstacles, steps or kerbs larger than specified in §7.
- When you stop on a (small) slope, use your brakes.
- Make sure all four wheel touch the ground while riding up or down a slope.
- Take slopes as slow as possible.
- Always stay on the pavement when riding on public roads.
- Pay attention if the road has holes or gaps that may cause entrapment of the wheels.
- Avoid stones and other objects that may block the wheels.
- Make sure that the footplate does not touch ground while taking an obstacle.
- Do not use your wheelchair/commode chair on an escalator.
- If available, wear your safety belt.
- Always keep the swing range of the footplate in mind to prevent bystanders from being injured or objects from being damaged.



- If you have not enough experience driving your wheelchair/commode chair, ask assistance of an attendant. Keep your arms away from the wheels and keep your feet on the footplates.
- Stairs should always be negotiated with the help of two attendants. Only lift the wheelchair/commode chair with the frame tubes.
- Never try to use stairs that are not appropriate for wheelchair/commode chairs.

Riding your wheelchair yourself (24" wheels):

- 1. Release the brakes.
- 2. Take both hand rims at their highest position.
- 3. Lean forward and push the hand rims forward until your arms are straight.

 Move your hands back to the top of the hand rims and repeat the movement

Assembly and adjustments

The instructions in this chapter are for the user and the specialist dealer.

To find a service facility or specialist dealer near you, contact the nearest Midmark facility.



- The wheelchair needs to be (dis)assembled and adjusted by a specialist dealer according to the instructions in this chapter.
- Only use parts and tools described in this manual.
- While (dis)assembling and operating the wheelchair, make sure no objects or body parts get caught between moving parts.
- Make sure all screws are firmly secured before driving.

Important remarks

- Be aware of the technical details and limits of intended use.
- For more information, contact Midmark.

Tools

To (dis)assemble and adjust the comfort chair/wheelchair, the following tools are needed:

- Wrench set no. 10
- Allen keyset n° 4



Scope of delivery

The following items are part of the delivery:

- · Framework with seat, wheels, armrests and leg rests
- Backrest
- Tools
- User manual

Before use, check if everything is included and that no products are damaged. Please note that the basic configuration may differ in different European countries. Contact your specialist dealer.

Assembly

The commode chair is delivered fully assembled, apart from the backrest. To install the backrest, put in into place and tighten the bolts to fasten.


Adjustments

- 1. **Seat width** Remove the seat by pulling it up and forwards from the frame tubes.
- 2. Remove the backrest.
- 3. On one side of the frame, remove the 3 screw-bolt connections (3) on the side of the seat frame tubes.
- 4. Slide the inner tubes inwards/outwards to the desired position (5 possible positions).
- 5. Replace the screw-bolt connections (3) and tighten firmly.
- 6. Repeat the steps above for the other side of the frame.
- 7. Replace the seat and backrest.

Please note that there is a corresponding seat cushion and backrest for each seat width.

Footrest length

- 1. Loosen socket screw (25) until the footrest (14) is released.
- 2. Slide the footrest (14) in/out of the leg-rest tube (12) to the desired length.
- 3. Tighten the socket screw (25) firmly.
- 4. Repeat this for the second footrest.
- 5. Make sure that both footrests are at the same height, and that they are firmly secured.




Assembly and adjustments





Maintenance

Points of maintenance



Repairs and replacements may only be undertaken by trained persons and only genuine replacement parts of Midmark should be used.

The service frequency depends on the frequency and intensity of use. Contact your dealer to agree to a common timetable for inspection/maintenance/repair. For the maintenance manual, refer to our website: www.midmark.com.

After use

Clean the bowl after each use, see §6.2.2.

Once a week

Clean the commode chair when needed after use, otherwise at least once a week.

Once every 6 months

Inspect the following points:

- All parts: Present and undamaged or unworn.
- All parts: Clean, see §6.2.2.
- Wheels, footrests and footplates: Well secured.
- Condition of wheels / tires, see §6.2.1;
- Condition of brakes, see §6.2.1
- Condition of frame: No deformation, instability, weakness or loose connections
- Condition of backrest folding mechanism: Properly working and locking.
- Condition of footrest mechanism: Properly working and locking.
- Condition of bowl and suspension system: Properly working and locking.
- Seat and backrest: No excessive wear (like dented spots, damage or tears).

Instructions for maintenance

Wheels and tyres

Proper working of the brakes depends on the state of the wheels or tyres, that can change due to wear and contamination (water, oil, mud, ...).

Keep your wheels free of wires, hair, sand and fibres.

Check the profile of the tyres, if applicable. If the tread depth is less than 1 mm, the tyres need to be replaced. Contact your specialist dealer for this matter.

Cleaning

Wipe all rigid parts of the wheelchair/commode chair with a damp cloth (not drenched). If necessary, use a mild soap, suitable for varnishes and synthetics.

The upholstery can be cleaned with lukewarm water and a mild soap. Do not use abrasive cleaning agents to clean.

After emptying the bowl in the toilet, rinse it with water and soap. Clean and dry it with toilet paper.



Disinfection

CAUTION Risk of damage

Disinfection of the commode chair may only be undertaken by trained persons. Consult your **s**pecialist dealer.

To disinfect the bowl, use a disinfectant suitable for PVC.

Troubleshooting



Risk of injuries and damage

NEVER attempt to repair the commode chair/wheelchair yourself.

The following symptoms may indicate a serious problem. Therefore, always contact your specialist dealer always if you spot any of following deviations:

- Strange sound.
- Uneven tread wear at one of the tyres.
- Jerky movements.
- Wheelchair/commode chair deflects to one side.
- Damaged or broken wheel assemblies.

End of use

At end of life, you need to dispose your wheelchair/commode chair according to the local environmental legislation. The best way to do so, is to disassemble the wheelchair/commode chair to facilitate the transport of recyclable parts.

Technical specifications

The technical details below are only valid for this wheelchair/commode chair, at standard settings and optimal ambient conditions. Take these details into account during use. The values are no longer applicable if your wheelchair/commode chair has been modified, damaged or suffers from severe wear.

Brand	MIDMARK
Туре	Wheelchair/commode chair
Model	1040C
Max. occupant mass	100 kg



Description	Dimensions
Model	1040C
Overall length with leg rest	850 mm
Overall width	520 – 560 – 590
	– 630 – 660 mm
Total height	1070 mm
Total mass	23,5 kg
Seat plane angle	2°
Effective seat depth	450 mm
Effective seat width	390 – 430 – 460 – 500 – 530 mm
Seat surface height at front edge	470 mm
Backrest angle	92° - 149°
Backrest height	580 mm
Footrest to seat distance	305 – 445 mm
Leg to seat surface angle	100° - 180°
Armrest to seat distance	260 mm
Front location of armrest structure	380 mm
Hand rim diameter	535 mm
Bucket content	5 litres
Swivelling wheels	
without brake	100x20 (2x)
with brake	100x20 (2x)
Wheels, Krypton model, soft	NA
Full wheels, 24" x 1 3/8" diameter	NA
Parking brake	On rear wheels
Primary use	Indoor only
Maximum safe slope	4,5°
Storage and use temperature	-25°C ~ +50°C
Storage and use humidity	0% ~ 90%
We reserve the right to introduce technical changes. Measurement tolerance ± 15 mm /1,5 kg / 1,5°.	



WARRANTY & SERVICE

Every effort has been made to ensure that the information in this user manual is valid. Midmark India Pvt. Ltd. reserves the right to change the information in this document without prior notice. Midmark India Pvt. Ltd. warrants, solely to the end users of this product that for a period specified in the warranty certificate, such product shall perform as per its intended use. The foregoing warranties shall not apply if the Product has been subjected to: (a) physical abuse, misuse, abnormal use, or use not consistent with

Midmark India Pvt. Ltd.'s published directions, (b) any modification by anyone other than Midmark India Pvt. Ltd. or third parties designated by Midmark India Pvt. Ltd.; or (c) fraud, tampering, negligence, or accidents, depending upon the nature of the products.

Limitation of Liability: In no event shall Midmark India Pvt. Ltd. be liable or obligated to the end user in any manner for any special, non-compensatory, consequential, indirect, incidental, statutory or punitive damages of any kind, including, without limitation, for injury or loss of life, lost profits, lost sales, lost revenue, loss of any software or data, or loss of use of any hardware, software or data, regardless of the form of action, whether in contract, tort, negligence, strict product liability, or otherwise, even if Midmark India Pvt. Ltd. has been informed of or is aware of the possibility of any such damages in advance. Midmark India Pvt. Ltd.'s total aggregate liability under this agreement and in relation to anything which Midmark India Pvt. Ltd. has done or not done in connection with this agreement shall be limited to the price of the products purchased and paid for by the end user during the period in which such liability arises. The limitations set forth above shall be deemed to apply to the maximum extent permitted by applicable law and notwithstanding the failure of the essential purpose of any limited remedies.

To maintain functional safety and the right to claim under the warranty only original replacement parts may be used. For ordering replacement parts, customer service requests and further questions, please contact our technical support department.



Disclaimer

Every effort has been made to ensure that the information in this user manual is valid. Midmark India Pvt. Ltd. reserves the right to change the information in this document without prior notice.

MANUFACTURER'S ADDRESS Corporate Office:

Midmark India Pvt. Ltd.

Art Guild House, "B" Wing, FOF, 4th, Phoenix Market City, B-16, Lal Bahadur Shastri Marg, Kurla West, Kurla, Mumbai, Maharashtra 400070

Tel.: +9122 2491 53000

Registered Office:

Janak House, opp. IOC Depot, Shaikh Misry Road, Wadala (E), Mumbai – 400037, India Tel:+9122 2413 0407

Toll Free No.: 1800 22 8020 | Email: technicalsupport@midmark.com



MIDMARK INDIA PVT. LTD.

Art Guild House, "B" Wing, FOF, 4th, Phoenix Market City, B-16, Lal Bahadur Shastri Marg, Kurla West, Kurla, Mumbai, Maharashtra 400070 | Toll Free: 1800 22 8020 | Tel: +91 22 4915 3000 | www.midmark.in | india@midmark.com